

Mean Well DIN Rail Power Supply

	PRODUCT #	WEIGHT	OUTPUT									INPUT			PROTECTION	DIMENSION	PRICE	Buy Now
			DC VOLTAGE	RATED CURRENT	CURRENT RANGE	RATED POWER	RIPPLE & NOISE (max.)	VOLTAGE ADJ. RANGE	VOLTAGE TOLERANCE	LINE REGULATION	LOAD REGULATION	FREQUENCY RANGE	EFFICIENCY (Typ.)	INRUSH CURRENT (Typ.)	OVER VOLTAGE	(WxHxD) (mm)		
1	DR-120-24	0.79 Kg	24V	5A	0~5A	120W	80mVp-p	24~28V	(±)1.0%	(±)0.5%	(±)1.0%	47~63Hz	84%	COLD START 20A/115VAC 40A/230VAC	29~33V	65.5x125.2x100	\$37.18	ADD TO CART
2	DR-15-12	0.1 Kg	12V	1.25A	0 ~ 1.25A	15W	120mVp-p	10.8 ~ 13.2V	(±)1.0%	(±)1.0%	(±)1.0%	47~63Hz	84%	COLD START 35A/115VAC 65A/230VAC	13.8 ~ 16.2V	25x93x56	\$12.09	ADD TO CART
3	DR-15-24	0.1 Kg	24V	0.63A	0 ~ 0.63A	15.2W	150mVp-p	21.6 ~ 26.4V	(±)1.0%	(±)1.0%	(±)1.0%	47~63Hz	85%	COLD START 35A/115VAC 65A/230VAC	27.6 ~ 32.4V	25x93x56	\$12.09	ADD TO CART
4	DR-30-12	0.27 Kg	12V	2A	0 ~ 2A	24W	120mVp-p	10.8 ~ 13.2V	(±)1.0%	(±)1.0%	(±)1.0%	47 ~ 63Hz	81%	COLD START 15A/115VAC 30A/230VAC	13.8 ~ 16.2V	78x93x56	\$15.15	ADD TO CART
5	DR-60-24	0.3Kg	24V	2.5A	0 ~ 2.5A	60W	150mVp-p	21.6 ~ 26.4V	(±)1.0%	(±)1.0%	(±)1.0%	47 ~ 63Hz	84%	COLD START 18A/115VAC 36A/230VAC	27.6 ~ 32.4V	78x93x56	\$22.03	ADD TO CART
6	DRH-120-24	0.75 Kg	24V	5A	0 ~ 5A	120W	80mVp-p	24 ~ 28V	(±)1.0%	(±)0.5%	(±)0.5%	47 ~ 63Hz	85%	COLD START 50A	30 ~ 36V	65.5x125.2x100	\$53.24	ADD TO CART
7	DRP-240-24	1.2 Kg	24V	10A	0 ~ 10A	240W	80mVp-p	24 ~ 28V	(±)1.0%	(±)0.5%	(±)1.0%	47 ~ 63Hz	84%	COLD START 27A/115VAC 45A/230VAC	30 ~ 36V	125.5x125.2x100	\$59.82	ADD TO CART
8	DRP-480-24	2.4 Kg	24V	20A	0 ~ 20A	480W	120mVp-p	24 ~ 28V	(±)1.0%	(±)0.5%	(±)1.0%	47 ~ 63Hz	89%	COLD START 40A/230VAC	30 ~ 36V	227x125.2x100	\$98.38	ADD TO CART
9	DRP-480S-24	2.6 Kg	24V	20A	0 ~ 20A	480W	120mVp-p	24 ~ 28V	(±)1.0%	(±)0.5%	(±)1.0%	47 ~ 63Hz	89%	COLD START 27A/115VAC 45A/230VAC	30 ~ 36V	227x125.2x100	\$103.58	ADD TO CART
10	DRT-240-24	1.3 Kg	24V	10A	0 ~ 10A	240W	80mVp-p	24 ~ 28V	(±)1.0%	(±)0.5%	(±)0.5%	47 ~ 63Hz	89%	COLD START 50A	30 ~ 36V	125.5x125.2x100	\$73.13	ADD TO CART
11	DRT-480-24	2.5 Kg	24V	20A	0 ~ 20A	480W	80mVp-p	24 ~ 28V	(±)1.0%	(±)0.5%	(±)0.5%	47 ~ 63Hz	89%	COLD START 50A	30 ~ 36V	227x125.2x100	\$103.89	ADD TO CART
12	MDR-20-5	0.19 Kg	5V	3A	0 ~ 3A	15W	80mVp-p	4.75 ~ 5.5V	(±)2.0%	(±)1.0%	(±)1.0%	47 ~ 63Hz	76%	COLD START 20A/115VAC 40A/230VAC	5.75 ~ 6.75V	22.5x90x100	\$15.15	ADD TO CART
13	MDR-60-24	0.33 Kg	24V	2.5A	0 ~ 2.5A	60W	150mVp-p	24 ~ 30V	(±)1.0%	(±)1.0%	(±)1.0%	47 ~ 63Hz	88%	COLD START 30A/115VAC 60A/230VAC	31.2 ~ 36V	40x90x100	\$22.64	ADD TO CART
14	SDR-120-24	0.67Kg	24V	5A	0 ~ 5A	120W	100mVp-p	24 ~ 28V	(±)1.0%	(±)0.5%	(±)1.0%	47 ~ 63Hz	91%	35A/115VAC 70A/230VAC	29 ~ 33V	40x125.2x113.5	\$59.67	ADD TO CART
15	SDR-240-24	1.03Kg	24V	10A	0 ~ 10A	240W	100mVp-p	24 ~ 28V	(±)1.0%	(±)0.5%	(±)1.0%	47 ~ 63Hz	94%	33A/115VAC 65A/230VAC	29 ~ 33V	63x125.2x113.5	\$94.86	ADD TO CART
16	SDR-480-24	1.6Kg	24V	20A	0 ~ 20A	480W	100mVp-p	24 ~ 28V	(±)1.2%	(±)0.5%	(±)1.0%	47 ~ 63Hz	94%	40A/115VAC 80A/230VAC	29 ~ 33V	85.5x125.2x128.5	\$146.88	ADD TO CART
17	WDR-120-24	0.65Kg	24V	5A	0 ~ 5A	120W	120mVp-p	24 ~ 29V	(±)1.0%	(±)0.5%	(±)0.5%	47 ~ 63Hz	91% / 400V	COLD START 50A	31 ~ 37V	40x125.2x113.5	\$64.26	ADD TO CART
18	WDR-240-24	1.06Kg	24V	10A	0 ~ 10A	240W	150mVp-p	24 ~ 28V	(±)1.0%	(±)0.5%	(±)1.0%	47 ~ 63Hz	91%	COLD START 50A	29 ~ 33V	63X125.2X113.5	Call for Pricing Price Quote Form	
19	WDR-480-24	1.7Kg	24V	20A	0 ~ 20A	480W	100mVp-p	24 ~ 28V	(±)1.0%	(±)0.5%	(±)1.0%	47 ~ 63Hz	92%	COLD START 50A	29 ~ 33V	85.5X125.2X128.5	Call for Pricing Price Quote Form	
20	MDR-20-24	0.19Kg	24V	1A	0 ~ 1A	24W	150mVp-p	21.6 ~ 26.4V	(±)1.0%	(±)1.0%	(±)1.0%	47 ~ 63Hz	84%	COLD START 20A/115VAC 40A/230VAC	27.6 ~ 32.4V	22.5X90X100	\$15.15	ADD TO CART